
P 534





PORTABLE AIR CONDITIONER

Product data sheet

Brand name		Qlima
Model	·	P 534
Sound power level ¹	dB(A)	65

Refrigerant GWP²

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 3. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 3 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

EER ²	W/W	2.67
EE-Class ²		A+
Indicative hourly electricity consumption (Qsd/c)	kW	1.2
Capacity (P rated) Cooling ²	kW	3.20

Product specifications

Colour	white
EAN code	8713508778150

Technical specifications

Power consumption Cooling	kW	1.2
Power consumption standby mode	W	0.5
Power supply	V/Hz/Ph	220-240 / 50 / 1
Current	A	5.3
Air flow ¹	m ³ /h	300
For rooms up to ¹	m ³	85-110
Dehumidification capacity ³	L/24 h	36
Operating range	°C	18-35
Thermostatic range	°C	18-32
Sound pressure level	dB(A)	57
Fan speed		3 positions
Control		electronic / remote
Refrigerant	type/charge (g)	R290 / 235
Refrigerant / GWP		3
CO ₂ equivalent	tonnes	0.001
Dimensions (w x d x h)	mm	440 x 355 x 715
Compressor type		rotary
Protection class	IP	X0
Weight	kg	31
Guarantee	years	2

- 1 To be used as indication
- 2 Measured conform EN 14511-2011
- 3 Moisture removal at 32°C, 80% RH

Accessories

1 Hose adapter		
1 Exhaust hose		
2 Hose connectors		
Remote control		
Manual	· · · · · · · · · · · · · · · · · · ·	

Most important spare parts

Spare part description EAN Code









20 ft = 144 40 ft = 288 HO = 432 W x D x H = 479 x 860 x 389 mm Gross weight = 35 kg



P 534 PORTABLE AIR CONDITIONER



Remote control with LCD-display



3 Fan speed settings



Cooldown effect



Environmental friendly refrigerant



Dehumidifcation function

Features

Wireless smart control:

The air conditioning is delivered with a convenient wireless smart control that enables a total control over your home comfort. Download the app and you can control your air conditioner with your smartphone from anywhere.

Electronic controls:

The unit is equipped with electronic touch controls.

Fan speed setting:

Select the fan speed: low, medium or high. The display will show the chosen speed.

Timer:

Operating time to be set up to 24 hours. The unit switches off or on automatically when the set time has run down.

Air conditioning:

The unit produces, with relatively high energy efficiency (A-rating), a pleasant and refreshing high capacity cool airflow. Unhealthy particles are captured by the air filters. Performance is optimal when the entering of warm outside air

Airflow:

Move the air vent direction by adjusting the grill at the front side of the air conditioner and by moving the vertical and horizontal louvers.

Cooldown effect

The unit removes humidity by condensation. The condensate cools the condenser and is removed by the hot air discharge. This will increase the energy efficiency; the so called "cool down" effect.

Dehumidification

The unit can also be used as dehumidifier only. In that case the exhaust hose is not connected and warm air returns in the room.

Continuous drainage:

In case of use as dehumidifier only it is necessary to connect a continuous drainage tube (not included) to the unit.

Exhaust duct:

Hot air and humidity is transported, by an easy to install exhaust duct, outside the room.

Full colour box:

The unit is delivered complete with auxiliary parts in a stylish full colour box showing application and operation information in multiple languages.

* Measured conform EN 14511